

CHARACTERISTICS

Weight: 0,725 Kg / 1,6 Lb
 Housing in ZAMAK
 Impeller in plastic UL 94 V-0
 L-10 life expectancy at 40°C: 80.000 hours
 Operating temperature range: -10 / +70 °C
 Storage temperature: -54 / +85°C
 Connection: Terminals
 Impedance Protected
 IP20



OPTIONS

Speed sensor
 Other IP levels
 Flying leads connection
 Salt spray protection
 Shocks and vibrations protection
 Marine application
 Wide temperature range
 Other voltages
 Dual voltage 115-230V

Part Number	Voltage		Frequency	Nb Phases	Airflow		Pressure		Nominal speed	Noise level LP	Nominal current	Starting current	power	Capacitor
	V	Hz			l/s	CFM	mm H ₂ o	inch H ₂ o						
125XL0182001	115	50	1	1	25,0	53,00	2,2	0,09	1600	30	135	145	12	
	82	60			27,0	57,24	2,4	0,09						
81	220	50	1	1	25,0	53,00	2,2	0,09	1600	30	75	90	12	
	81	60			27,0	57,24	2,4	0,09						
125LG0182001	115	50	1	1	35,0	74,20	5	0,20	2200	38	200	260	16	
	82	60			40,0	84,80	5,5	0,22						
81	220	50	1	1	35,0	74,20	5	0,20	2200	38	110	140	18	
	81	60			40,0	84,80	5,5	0,22						
125XR0182001	115	50	1	1	44,0	93,28	9,5	0,37	2800	44	200	310	16	
	82	60			53,0	112,36	10,5	0,41						
81	220	50	1	1	44,0	93,28	9,5	0,37	2800	44	125	170	18	
	81	60			53,0	112,36	10,5	0,41						

