



# AXIAUX DC

| Dimensions        |                      | Tension         | Débit libre |           | Pression maximum |             | Niveau sonore | Normes et directives | Image | Code      |
|-------------------|----------------------|-----------------|-------------|-----------|------------------|-------------|---------------|----------------------|-------|-----------|
| 80 x 80 x 25 mm   | 3,15 x 3,15 x 1 "    | 12V             | 14,88l/s    | 31,55CFM  | 4,45mmH2O        | 0,18inchH2O | 34,2dBA       | CE UL RoHS           |       | 146DH-S   |
|                   |                      | 12V- 24V - 48V  | 22l/s       | 46,64CFM  | 10,89mmH2O       | 0,43inchH2O | 44dBA         | CE UL RoHS           |       |           |
| 92 x 92 x 38 mm   | 3,62 x 3,62 x 1,5 "  | 24V             | 31,4l/s     | 66,57CFM  | 20,19mmH2O       | 0,79inchH2O | 51,8dBA       | -                    |       | 99YH-S    |
| 120 x 120 x 32 mm | 4,72 x 4,72 x 1,26 " | 12V - 24V - 48V | 35,3l/s     | 74,84CFM  | 23,96mmH2O       | 0,94inchH2O | 54,6dBA       | -                    |       |           |
|                   |                      |                 | 27l/s       | 57,24CFM  | 2,24mmH2O        | 0,09inchH2O | 29,5dBA       | CE UL RoHS           |       | 158D      |
|                   |                      |                 | 39l/s       | 82,68CFM  | 4,79mmH2O        | 0,19inchH2O | 37,5dBA       | CE UL RoHS           |       |           |
|                   |                      |                 | 49l/s       | 103,88CFM | 7,44mmH2O        | 0,29inchH2O | 42,5dBA       | CE UL RoHS           |       |           |
| 120 x 120 x 38 mm | 4,72 x 4,72 x 1,5 "  | 110V            | 55,9l/s     | 118,51CFM | 9,69mmH2O        | 0,38inchH2O | 45,5dBA       | CE UL RoHS           |       | 125DH     |
|                   |                      |                 | 49l/s       | 103,88CFM | 7,44mmH2O        | 0,29inchH2O | 42,5dBA       | -                    |       |           |
| 120 x 120 x 38 mm | 4,72 x 4,72 x 1,5 "  | 12VDC           | 46l/s       | 97,52CFM  | 8mmH2O           | 0,31inchH2O | 45dBA         | CE RoHS              |       | 125YG     |
|                   |                      | 24VDC           | 46l/s       | 97,52CFM  | 8mmH2O           | 0,31inchH2O | 45dBA         | CE RoHS              |       |           |
|                   |                      | 48VDC           | 46l/s       | 97,52CFM  | 8mmH2O           | 0,31inchH2O | 45dBA         | CE RoHS              |       |           |
| 120 x 120 x 38 mm | 4,72 x 4,72 x 1,5 "  | 12V - 24V - 48V | 27l/s       | 57,24CFM  | 2,52mmH2O        | 0,1inchH2O  | 30dBA         | CE RoHS              |       | 125D_A    |
|                   |                      |                 | 39l/s       | 82,63CFM  | 5,27mmH2O        | 0,21inchH2O | 38dBA         | CE RoHS              |       |           |
|                   |                      |                 | 49l/s       | 103,81CFM | 8,32mmH2O        | 0,33inchH2O | 43dBA         | CE RoHS              |       |           |
|                   |                      |                 | 53l/s       | 112,29CFM | 9,75mmH2O        | 0,38inchH2O | 46,2dBA       | CE RoHS              |       |           |
|                   |                      |                 | 61,10l/s    | 129,45CFM | 13,52mmH2O       | 0,53inchH2O | 48,8dBA       | CE RoHS              |       |           |
| 172 x 150 x 38 mm | 6,77 x 5,9 x 1,5 "   | 12V             | 69,44l/s    | 147,12CFM | 19,21mmH2O       | 0,76inchH2O | 52,6dBA       | CE RoHS              |       | 121D-148D |
|                   |                      |                 | 110l/s      | 233,2CFM  | 12,5mmH2O        | 0,49inchH2O | 57dBA         | CE UL RoHS           |       |           |
|                   |                      |                 | 24V         | 105l/s    | 222,6CFM         | 22,5mmH2O   | 0,89inchH2O   | 62dBA                |       |           |
|                   |                      | 28V             | 112l/s      | 237,44CFM | 12mmH2O          | 0,47inchH2O | 58dBA         | CE UL RoHS           |       |           |
|                   |                      |                 | 120l/s      | 254,4CFM  | 32,51mmH2O       | 1,28inchH2O | 66dBA         | CE UL RoHS           |       |           |
|                   |                      |                 | 120l/s      | 254,4CFM  | 32,5mmH2O        | 1,28inchH2O | 66dBA         | CE UL RoHS           |       |           |
|                   |                      |                 | 112l/s      | 237,44CFM | 12mmH2O          | 0,47inchH2O | 58dBA         | CE UL RoHS           |       |           |
|                   |                      | 110V            | 112l/s      | 237,44CFM | 12mmH2O          | 0,47inchH2O | 58dBA         | CE UL RoHS           |       |           |